

Serial No.: 09/460,688

Attorney Docket No: MCS-117-99

IN THE CLAIMS

Please cancel claims 1, 2, 15, 32 and 33 without prejudice.

Please amend claims 3, 4, 5, 14 and 16 as follows:

1. (Canceled)

2. (Canceled)

3. (Currently Amended) ~~The method of claim 2,~~ A method of simulating connection characteristics of a network, comprising:  
providing a driver capable of accessing a stream of network packets;  
calculating a send time for each of the network packets and attaching the respective send time to the corresponding packet;  
sequencing the network packets in a queue until the respective send times to simulate a desired propagation connection characteristic;  
deleting the send time from each network packet when the packet is removed from the queue; and  
altering the stream of network packets to simulate an additional connection characteristic of the network;  
wherein the propagation connection characteristic is at least one of: (a) bandwidth; (b) transmission delay;  
wherein the additional connection characteristic of the network is at least one of: (a) loss of a network packet; (b) fragmentation of a network packet; (c) reordering of at least two network packets; (d) duplication of a network packet; (e) network address translation of a network packet having an original network address.

4. (Currently Amended) ~~The method of claim 2,~~ A method of simulating connection characteristics of a network, comprising:

Serial No.: 09/460,688

Attorney Docket No: MCS-117-99

providing a driver capable of accessing a stream of network packets;  
calculating a send time for each of the network packets and attaching the  
respective send time to the corresponding packet;  
sequencing the network packets in a queue until the respective send times  
to simulate a desired propagation connection characteristic;  
deleting the send time from each network packet when the packet is  
removed from the queue; and  
altering the stream of network packets to simulate an additional  
connection characteristic of the network;  
wherein the propagation connection characteristic is at least one of: (a)  
bandwidth; (b) transmission delay;  
wherein simulating a desired bandwidth comprises:  
determining a length of a network packet;  
calculating the send time for the network packet using the network  
packet length to simulate the desired bandwidth.

5. (Currently Amended) The method of claim 2, A method of simulating  
connection characteristics of a network, comprising:  
providing a driver capable of accessing a stream of network packets;  
calculating a send time for each of the network packets and attaching the  
respective send time to the corresponding packet;  
sequencing the network packets in a queue until the respective send times  
to simulate a desired propagation connection characteristic;  
deleting the send time from each network packet when the packet is  
removed from the queue; and  
altering the stream of network packets to simulate an additional  
connection characteristic of the network;  
wherein the propagation connection characteristic is at least one of: (a)  
bandwidth; (b) transmission delay;  
wherein simulating a desired transmission delay comprises adding the  
desired transmission delay to the send time.

Serial No.: 09/480,688

Attorney Docket No: MCS-117-99

6. (Original) The method of claim 3, wherein altering the stream of network packets to simulate the network address translation of the network packet comprises:  
generating a simulated network address for each new connection; and  
mapping the original network address to the simulated network address  
for each network packet.

7. (Original) The method of claim 6, wherein the simulated network address is generated randomly.

8. (Original) The method of claim 3, wherein altering the stream of network packets to simulate the loss of a network packet comprises:  
determining a packet dropping frequency; and  
deleting the network packet at the packet dropping frequency.

9. (Original) The method of claim 3, wherein altering the stream of network packets to simulate the fragmentation of the network packet comprises:  
determining a packet fragmentation frequency;  
separating the network packet into a plurality of new network packets at the packet fragmentation frequency;  
dividing data contained in the network packet; and  
distributed the divided data between the new network packets.

10. (Original) The method of claim 9, further comprising creating headers for the new network packets.

11. (Original) The method of claim 9, wherein the divided data is distributed disproportionately between the new network packets.

12. (Original) The method of claim 3, wherein altering the stream of network packets to simulate the reordering of at least two network packet comprises:

Serial No.: 09/480,688

Attorney Docket No: MCS-117-99

determining a packet reordering frequency; and  
changing an order of the at least two network packets within the network packet stream at the packet reordering frequency.

13. (Original) The method of claim 3, wherein altering the stream of network packets to simulate the duplication of the network packet comprises:

determining a packet duplication frequency; and  
generating a copy of the network packet at the packet duplication frequency.

14. (Currently Amended) ~~The method of claim 2;~~ A method of simulating connection characteristics of a network, comprising:

providing a driver capable of accessing a stream of network packets;  
calculating a send time for each of the network packets and attaching the respective send time to the corresponding packet;  
sequencing the network packets in a queue until the respective send times to simulate a desired propagation connection characteristic;  
deleting the send time from each network packet when the packet is removed from the queue; and  
altering the stream of network packets to simulate an additional connection characteristic of the network;  
wherein the propagation connection characteristic is at least one of: (a) bandwidth; (b) transmission delay;  
wherein altering the stream of network packets comprises changing a network address of each client connection.

15. (Canceled)

16. (Currently Amended) ~~The method of claim 15;~~ A method of simulating connection characteristics of a network, comprising:

providing a driver capable of accessing a stream of network packets;

Serial No.: 09/460,688

Attorney Docket No: MCS-117-99

calculating a send time for each of the network packets and attaching the respective send time to the corresponding packet;

sequencing the network packets in a queue until the respective send times to simulate a desired propagation connection characteristic;

deleting the send time from each network packet when the packet is removed from the queue; and

altering the stream of network packets to simulate an additional connection characteristic of the network;

wherein the driver is implemented in an intermediate layer between an upper layer and a lower layer;

wherein the upper layer processes the network packets and the lower layer places the network packets onto a physical media of the network.

17. (Canceled)

18. (Previously Presented) The method of claim 6, wherein the mapping is performed using a two-way mapping table.

19. (Original) The method of claim 18, wherein the two-way mapping table is a two-way hash table.

20. (Original) The method of claim 19, wherein the mapping uses a two-way output hash table, a two-way input hash table and a hash information repository.

21. (Original) The method of claim 18, wherein the mapping uses a two-way output mapping table if the network packet is being transmitted and a two-way input mapping table if the network packet is being received.

Claims 22-38. (Canceled)

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.